



Impact solutions for business
and logistic environments

Compuprint 2056N

Lan Ready

Compuprint 2056N satisfies typical needs in hospitals, hotels, retail stores, as well as in industrial and logistics environments. To these modern needs belongs the network capability what is indicated by the "N" of 2056N.

As a very economical printer the Compuprint 2056N helps to save money with its longlife ribbon of 10 million characters and its low power consumption.

Compuprint 2056N is the best choice for printing applications using multipart forms, single sheets, labels and envelopes.

Values and Features

- ✓ 24 pins print head (up to 500 Mio. strokes/pin)
- ✓ team player thanks to Ethernet 10/100 Base-T
- ✓ 4 interfaces in total: parallel, Ser, USB 2.0 & Ethernet
- ✓ great impact: 1 + 5 copies
- ✓ up to 480 characters/second
- ✓ Workload: up to 20.000 pages a month
- ✓ Automatic pin alternation



Versatile, economic and reliable

The Compuprint 2056N is most economic both in terms of its price and on duty. With an easy to use operator panel, low printing noise and multiple interfaces included as standard the Compuprint 2056N is user friendly.

The Compuprint 2056N brings higher levels of print quality to general business and point of sale applications producing invoices, receipts, dispatch notes, labels and end of day reports.



Compuprint 2056N – Your most economic network printer

Printer Model 2056N

Print Technology	Serial Dot Matrix Printer
Printhead	24 pins (Ø 0,22 mm)
Print Speed	10 cpi: High Speed Draft 480 cps, Draft 400 cps, NLQ 200 cps 12 cpi: High Speed Draft 576 cps, Draft 480 cps, NLQ 240 cps
Print Width	Max. 80 columns @ 10 characters/inch
Paper Handling	+ Continuous Form: rear loading – paper width: 56 – 267 mm + Cut Sheet: paper width: 48 – 261 mm, weight: 52 – 90 g/m2 + Label: width of liner 101,6 – 254 mm, smallest label: 63.5 mm x 23.8 mm weight: max. 68 g/m2
Copies	1+ 5 - max. thickness: 0.52 mm
Special Functions	+ Automatic pin alternation (for decrease the workload on pins used most frequently) + smart pin surveillance to substitute broken pins + Printer configuration by remote control (PC-Software)
Graphic Resolution	360 dpi x 360 dpi
Vertical Spacing	6 lines per inch; 8 lines per inch; n/360 per inch
Horizontal Spacing	10, 12, 15, 17, 20 cpi and proportional
1D-Codes (Barcodes)	EAN 8, EAN 13, 2/5 Interleaved, 2/5 Matrix, 2/5 Industrial, Code 39, Code 128, NW-7
Fonts	Draft, Courier, OCR-A, OCR-B, Prestige, Presentor, Roman, Sans Serif, Script
Character Sets	17 international character sets: U.S.A, France, Germany, U.K, Denmark 1 & 2, Sweden, Italy, Spain 1 & 2, Japan, Norway, Latin Am, Korea, Legal, Netherlands, Turkey IBM and EPSON character sets: CP 437 (USA), CP437G (Greek), CP850 (Multilingual), CP851 (Greek), CP852 (Eastern Europe), CP853 (Turkish), CP855 (Cyrillic), CP 861 (Island), CP863 (French-Canadian), CP860 (Portugal), CP865 (Danish-Norwegian), CP866 (Russian), CP1250 (Latin2 Windows), CP1252 (Latin1 Windows), CP1253 (Greek Windows), MAZOWIA, KAMENICKY, ISO Latin 1, 2, 7, 9, BULGARIA, HUNGARY, ARAB NLS, ARAB EXT, KBL
Emulation	Epson ® LQ ESC/P2, IBM ® Personal Printer 2391
Driver	Windows 2000/XP/7/8 Server 2003/2008
Interfaces	Parallel IEEE1284 bidirectional, Serial RS-232, USB 2.0 (Full Speed), Ethernet 10/100 Base-T
Buffer	132 KB
Print head life	500 Mio strokes/pin
Ribbon life	Black ribbon, > 10 Mio. Characters in draft
MTBF	> 20.000 hours
Noise	< 53 dB (A) (ISO 7779 Standard)
Power Supply	Std: 176 – 242 V - (100V – 110 V on request) Frequency: 50 Hz - (60 Hz 110 V)
Power Consumption	Printing: 70 W on average, Standby: 4,6 W
Dimensions	Depth: 28,0 cm, Width: 38,4 cm, Height: 13,9 cm
Weight	6 kg

Printer and Supplies

Compuprint 2056N with Par.,Ser, USB 2.0 ,Ethernet	PRT2056N
Black ribbon, 10 Mio. char in draft	PRK2050-1

Compuprint

Via Cottolengo,77
10072 Caselle T.se (TO)
ITALY
Phone: +39- 011-9892133
sales@compuprint.com
www.compuprint.com

