



H25



+ Related products



H15

- Windows CE
- Laser barcode scanner
- Bluetooth, W-LAN (WiFi)
- IP 54



OPH1004

- Batch Terminal
- Barcode laser scanner
- IrDA
- IP 54



PHL8112

- Windows CE
- Barcode laser scanner
- Bluetooth, W-LAN (WiFi), serial connector
- IP 65

Operation

- CPU: Marvell® PXA130 32-bit RISC 624Mhz
- O/S: Windows CE 6.0 Professional

Memory

- FlashROM: 256 MB
- RAM: 128 MB
- Expansion: User accessible microSD

Display

- Type: Transmissive Graphic TFT with 4-wire resistance touch panel, with adjustable backlight
- Size: 2.8", 240 x 320 pixels
- Mode: Portrait

Operating indicators

- Visual: 2 LED (red/green scanning indication & charging indicator)

Operating keys

- Entry options: Entry options: 23 keys total, 12 (alpha)numeric keys, 4 navigation keys, 4 function keys, 1 power key, 1 clear key, 1 scan key

Power

- Rechargeable battery: Lithium-Ion 3.7V 1840mAh
- High-capacity battery: Optional 3.7V 2760mAh
- Backup battery: 1 integrated rechargeable backup battery

Durability

- Temperature in operation: -10 to 50 °C / 14 to 122 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Humidity in storage: 5 - 95% (non-condensing)
- Drop test: 1.2 m / 4 ft drop onto concrete surface
- Protection rate: IP 65

Physical

- Dimensions (w x h x d): 62 x 144 x 26.2/35.8 mm / 2.44 x 35.67 x 1.03/1.41 in
- Weight body: Ca. 232 g / 8.2 oz (incl. battery)
- Case: Black

Enclosed items

- Standard battery 3.7V 1840mAh
- USB client cable
- Hand strap
- Getting started disc
- Stylus + cord

Sold separately

- High-capacity battery Lithium-Ion 3.7V 2760mAh
- Holster

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Villanova di Castenaso (BO)
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Brazil:** São Paulo

- **Japan:** Warabi City
- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** West Ryde

Opticon Sensors Europe B.V
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON
WWW.OPTICON.COM